

Product Specifications	
Panel Size/Type	17" L CD
	0.264mm x 0.264mm
Native/Optimum Resolution	
Maximum Resolution	
Response Time	
Contrast Ratio	
Brightness	
Viewing Angles	
710111197119100	Vertical: 160°
Display Colors	16.2 Million Colors (8bit)
	13.3" x 10.7" (337.9mm x 270.4mm)
Aspect ratio	
Input Signal	
,	
	Horizontal: 30kHz~80kHz, Vertical: 50~75Hz
Input PC Module	D-Sub x 15-pin (Analog RGB Input)
	Audio in 3.5mm head phone jack
Input Video Module	N/A
Audio	2W Stereo Speaker
Compatible Signals	VESA 1280 x 1024 @ 75/60Hz, VESA 1024 x 768 @ 75/70/60Hz
	VESA 800 x 600 @ 75/72/60/56Hz
	VESA 640 x 480 @ 75/60Hz, Super VGA, VGA,
	Standard 1280 x 768/60Hz,
	Mac 832 x 624 @ 75Hz, Power Mac and more
HD Compatible	
Controls	Back Panel Controls: Power/Menu, Adjustment +/-
	3 button OSD Controls: Contrast, Brightness, Volume, Auto Adjust, H-V Position, Language,
	Frequency, Phase, Color, Recall, Exit
	VESA DDC 1/2B compliance
Vesa Mount Hole	
	Tilt, 5° Forward, 90° Backward,
Dimensions (W X H X D)	380mm x 387mm x 190mm, 15" x 15.3" x 7.5"
Dimensions Boy/W v H v D)	438mm x 516mm x 110mm, 17.3" x 20.3" x 4.4"
•	Net: 3.4kg, 6.8 lbs
weight	Gross: 4.7kg, 9.4 lbs
Power Supply	Power Input AC: 100 ~ 240 V, 47/63Hz
	On: <35W; Active Off: <1W
	EPA Energy Star® Compliant
	FCC(B), UL, CE Energy Star , TCC'99 compliant
	Operating Temperature: -4° to 140° (-20°C to 60°C)
Environmental conditions	Operating Humidity: 5% to 90% (no condensation)
Warranty	3 Year Warranty
Transmity	o roa rranany



## **LCD Series**

Mid Level, 3 Year Warranty, Exceptional Image Quality Available Thru: Systems Builders, Value Added Resellers Ideal for: End-Users, Small/Medium Businesses, Education, Government, Dental or Doctor's Offices

**LCD1708** 

## **PRINCETON**

3300 Irvine Ave. Suite 120 Newport Beach, CA 92660 Tel: (949) 777-3379 Fax: (949) 777-3370

www.princetongraphics.com



\* 6 6 3 5 5 5 0 0 7 3 8 4 \*

UPC: 663555007384 14AP1729A00